

MD Weighing Indicator



Features

- Upto 1/100,000 display resolution
- Counting function delivers precise piece counting. Preprogrammed reference sample quantities of 5, 10, 20, 50...1000 parts.
- The indicator can be calibrated in Triple, double or single accuracy. To give an example you can make a platform scale 100kg with range like 10kg x 1g, 50kg x 5g and 100kg x 10g. Max resolution in each range can be 10,000 divisions.
- Hi Low Limit set points can be set for check weighing function. Once the limit is crossed the buzzer beeps and alarm is generated.
- An optional customer side dual display with 8-12m cable can be directly attached with the K9 series mounted display.
- Special LED display filter gives a very clear display. The display is even visible in direct sunlight with visibility levels of close to 20%-30%. LCD Display available with AMBER back-light
- Support for upto 4 x 350Ω loadcells
- 100% Tare Range, Auto zero, Sleep Mode
- 220V AC/built-in 6V rechargeable battery 50hr backup
- Weight hold function.



Back View

Specifications	Display Range	Selectable [-199999 ~ 999,999]	Internal Resolution	560,000 (Display) / 20Bit Internal
	Graduation	Selectable [1,2,5,10,20,50,100,200,500]	Output Mode	Continuous, Command, Printer(optional)
	Max Resolution	30K(Single)/15K (Double)/10K(Triple)	Power	SMPS 90-300V @ 50Hz / 6V 4Ah Batt
	Zero range	20% of Full Capacity	Operating Temp.	50° to 98° F / 0° to 45° C
	Calibration	Digital with external weight	Dimensions	240.5 x 114 x 179.5 mm (w x d x h)
	Display Type	Bright LED 0.56" / LCD Backlight	Gross Weight	2.1kg excluding battery



SEEGATE CORPORATION

Swastik House , Building No.382 , 3rd Floor,
Room No.7 , Near Lamington Road Police
Station , Grant Road (E) . Mumbai -400007.

Tel - 022-40044443 Mobile - 7021525891 , 797338650

Email -sales@seegatecorp.com. Website - www.seegateloadcell.com